

extension boom kit NAARVA) for 5-8 ton excavators



Features

- Boom with rotator and valves
- Mounting to the place of bucket. Available with all bucket coupling types.
- Support foot helps moving around with excavator.

Suitable for

• 5 - 8 ton excavators

Easy and effortless installation

Extension boom mounts like a digging bucket. It is available with all most common bucket coupling types. Extension boom kit is a complete installation kit ready for use.

Excavator has high pressure. That is why the pressure is reduced with a double safety valve to 170-200 bar. You need two way hydraulics to control Naarva and the rotator. Naarva harvesters and felling heads require only one two directional valve for control. Rotator also requires a two directional valve. Most excavators don't have an extra valve for the control of rotator. Extension boom kit includes a 6 way valve that guides the oil flow to rotator instead of Naarva when a button is pressed.







Baltrotors GR46 rotator

Press button, 6 way valve and double safety valve



TECHNICAL SPECIFICATIONS

Product	JP23 extension boom	JP25 extension boom
Reach	125 cm	156 cm
Total length	204 cm (foot 85 cm, boom 125 cm)	252 cm (foot 103 cm, boom 156 cm)
Weight	200 kg	207 kg
Contents	Boom with support foot, suitable bucket coupling, Baltrotors GR46 rotator and swing damper, 6-way valve and press button for rotator, safety valve	Boom with support foot, suitable bucket coupling, Baltrotors GR46 rotator and swing damper, 6-way valve and press button for rotator, safety valve
Control	1 press button for rotator. Cable must be drawn from boom to cabin.	1 press button for rotator. Cable must be drawn from boom to cabin.
Warranty	12 months	12 months

MANUFACTURER



Pentin Paja Oy Pamilonkatu 30 80130 Joensuu Finland SPARE PARTS AND TECHNICAL SUPPORT

Janne Häikiö +358 40 733 0405 Joonas Häikiö +358 400 298966 email:

info@pentinpaja.fi

www.naarva.fi

MANUFACTURER RESERVES RIGHT TO CHANGES 12/2015